



Norsat
International Inc.

Intelligent Satellite Solutions



LNB

C-BAND PLL

3000

HIGH STABILITY



TYPICAL SPECIFICATIONS

Noise temperature	20K to 30K depending on model number
L.O. stability (over temperature excl offset)	± 2 kHz to ± 25 kHz depending on model number
Phase noise (SSB)	-73 dBc/Hz at 1kHz -83 dBc/Hz at 10kHz -93 dBc/Hz at 100kHz
Input VSWR	2.2 : 1
Output VSWR	2.2 : 1

Conversion gain	62 dB
Output P1dB	9 dBm
Power requirements	+15 to +24 V supplied through center conductor of IF cable
Current drain	330 mA
Input Waveguide	CPR229G
Dimensions	144 (L) x 70 (W) x 98 (H) mm (5.7 x 2.8 x 3.9 in)
Weight	500 g / 17.6 oz
Temperature Range	-40°C to +60°C
Relative Humidity	0 - 100% condensing

FREQUENCY BANDS AVAILABLE


Input frequency (GHz)	3.40 to 4.20
L.O. frequency (GHz)	5.15
Output frequency (MHz)	950 to 1750

HOW TO ORDER

3120N

CONNECTOR	F - 75 Ohm N - 50 Ohm
NOISE TEMPERATURE	20 - 20 K 25 - 25 K 30 - 30 K
L.O. STABILITY	0.4 ppm - ± 2 kHz 0.6 ppm - ± 3 kHz 0.8 ppm - ± 4 kHz 1.0 ppm - ± 5 kHz 2.0 ppm - ± 10 kHz 5.0 ppm - ± 25 kHz
LNB SERIES #	

MECHANICAL DIAGRAM



Norsat
International Inc.

Americas
tel + 1.800.644.4562
fax + 1.604.821.2801

Asia
tel + 1 604.821.2835
fax + 1 604.821.2801

Europe, Middle East & Africa
tel + 44.1522.730800
fax + 44.1522.730927

Online
info@norsat.com
www.norsat.com